

C Operator Precedence and Associativity

<i>Operator</i>	<i>Description</i>	<i>Associativity</i>
() [] . -> ++ --	Parentheses (function call) (see Note 1) Brackets (array subscript) Member selection via object name Member selection via pointer Postfix increment/decrement	left-to-right
++ -- + - ! ~ (type) * & sizeof	Prefix increment/decrement Unary plus/minus Logical negation/bitwise complement Cast (change type) Dereference Address Determine size in bytes	right-to-left
* / %	Multiplication/division/modulus	left-to-right
+ -	Addition/subtraction	left-to-right
<< >>	Bitwise shift left, Bitwise shift right	left-to-right
< <= > >=	Relational less than/less than or equal to Relational greater than/greater than or equal to	left-to-right
== !=	Relational is equal to/is not equal to	left-to-right
&	Bitwise AND	left-to-right
^	Bitwise exclusive OR	left-to-right
	Bitwise inclusive OR	left-to-right
&&	Logical AND	left-to-right
	Logical OR	left-to-right
?:	Ternary conditional	right-to-left
= += -= *= /= %= &= ^= = <<= >>=	Assignment Addition/subtraction assignment Multiplication/division assignment Modulus/bitwise AND assignment Bitwise exclusive/inclusive OR assignment Bitwise shift left/right assignment	right-to-left
,	Comma (separate expressions)	left-to-right

Note 1: Parentheses are also used to group expressions to force a different order of evaluation; such parenthetical expressions can be nested and are evaluated from inner to outer.