

ECE 435 – Network Engineering

Lecture 21

Vince Weaver

`http://web.eece.maine.edu/~vweaver`

`vincent.weaver@maine.edu`

27 November 2018

Announcements

- HW#9 was posted
- Project Status
 - One e-mail per group
 - One-line summary of project topic
 - Brief update on how it is going
 - Whether you're willing to present on Tuesday vs Thursday



Homework #8 Review

- Questions

1. S/N is 500. $db=10 \log S/N$, roughly 27dB

2. 100MHz, 14dB, Shannon? (typical nums cat5 twisted pair)

$$\text{bps} = H \log_2 (1 + S/N)$$

$$S/N = 25, \text{bps} = 100M * \log_2(1+25) = 470\text{Mb/s}$$

3. Fiber over copper

Speed? This varies, Electrons in copper 50-90% of speed of light, Light in fiber 70-90%



4. Satellite over fiber:

no need to run cables everywhere

Can broadcast over greater area

5. Fiber over satellite:

less secure (easier to tap)

longer latency

Cost? Which is more expensive?

faster?

6. FCC won't let me be

Though they only regulate consumer, federal govt (like military, FAA, etc, NTIA National Telecommunications



and Information Administration) 4.3GHz airport/radio navigation

FCC database lists numerous companies, but they don't own freq, just have license to make radio altimeters



Why might you want to split up LANs

- Bandwidth concerns
- Different groups, privacy/security
- Equipment costs
- Distance
- Reliability (equipment failure)



Bridging

- How do you connect together multiple groups of machines into one big LAN?
- An interconnection at the link layer is called a MAC bridge, or bridge. Also a Layer-2 switch
- IEEE 802.1D
- Transparent bridge, as users are not aware of them
- Bridge acts in promiscuous mode (receives every frame



on the LAN) so it can find ones that need to forward on across the bridge

- How does bridge learn the MAC addresses? self-learning. It watches for frames coming in and their source address. Puts in table. How does it learn where destination is? It broadcasts to all. Once the destination also sends a frame (so its source is known) then the switch updates its table and no longer broadcasts.
- How do you handle machines that are moved? Aging mechanism. If not heard from for a while, expire the



table

- Multicast or Broadcast, can follow GMRP or GARP to limit how far it is broadcast



Bridge vs Switch

- Before 1991 a switch was a bridge (in the standard)
- In 1991 Kalpana made a “switch” and differentiated it by cut-through instead of store and forward
- Store and forward – whole frame received before resent
larger latency, no problem with broadcast, can check FCS
- cut-through – can start transmitting before receiving completely (destination MAC at beginning). Slightly



better latency, broadcast not possible, too late to check FCS

- These day most are store and forward
- Differences
 - repeater – purely electronic, resends voltages (original Ethernet allowed four)
 - hubs – frames coming in one port sent to all others creates a collision domain
 - bridge – connects two or more LAs. Each line own collision domain



can maybe bridge different types of networks
(Ethernet/token, wired/wireless)

- switch – point-to-point frame routing, sort of like one bridge per port
- router – higher layer, actually strips off headers and looks at packets



Spanning Tree Protocol

- Invented by Radia Perlman at DEC
- Can have problems if cause a loop in the topology.
Frames can circulate loop forever
- Why have a loop then? Redundancy.
- 802.1D
 - Each switch and port assigned an ID with priority
 - Each link assigned a cost, inversely proportional to link speed
 - The lowest ID gets to act as root (there is a protocol



- on how to elect the root)
- Each LAN connected to upstream port in active topology, called the dedicated port. Receives from root port
 - Config info comes from root as bridge protocol data unit (BPDU) on reserved multicast address 01:80:c2:00:00:00
 - Switch may configure itself based on BPDU.
 - Can take 30-50s to notice failure
 - 802.1w – Rapid Spanning Tree Protocol
 - Modern replacement



- Can detect failure in milliseconds



Bridging 802.11 to 802.3

- Note, describe this after wireless?
- Need to strip off one header, put new one on
- Need to put fields in as needed, recalc checksum, etc
- What if bridging faster net to slower one
- What if maximum frame size different on different LANs?
Can't always fragment
- What if one has encryption and one doesn't
- What of quality of service?



VLAN

- How to switch machines between networks? Request?
Someone in wiring closet?
- Physical LAN
- What if want to partition a switch so some nodes are on one and one on another (virtual LANs)
- IEEE 802.1Q
- can have priority



- link aggregation, combine two links for higher bandwidth
- why split up?
 - Security (someone in promisc mode not see everything)
 - Load – two groups, one not happy if other group takes up all bandwidth
 - Broadcasting – when asks for a connection, broadcasts to all
 - broadcast storms – entire LAN brought down with all machines broadcasting
- how to bridge VLANs? special VLAN field in Ethernet



frame

priority, CDI (makes connectionless interface have some manner of connection)

