

Index

1

16×32 multiply and accumulate, 635
16-bit multiply, 627

3

32×32 multiply and accumulate, 635

6

64-bit addition, 213
64-bit logical shift left, 216
64-bit multiplication, 218
64-bit operations, 213
64-bit shift left, 216
64-bit shift right, 217
64-bit sign extension, 215
64-bit signed division, 221
64-bit subtraction, 214
64-bit unsigned division, 219

A

ABI, 174, 179
access C variables, 242
ACK, 540, 542, 544, 545
active high, 409
active low, 409
ADC, 151, 475
 calibration, 497
 continuous mode, 481
 data alignment, 483
 digital quantization, 476
 DMA, 493
 external trigger, 486
 freeze mode, 486
 injected group, 482
 input channel, 482
 input channels, 484
 JEOC, 489
 LSB voltage, 479
 ping-pong buffering, 495
 power dissipation, 475
 quantization error, 479

 regular group, 482
 resolution, 475
 sample-and-hold amplifier, 477
 sampling error, 478
 sampling rate, 475
 sampling time, 478
 scan mode, 482
 single mode, 481
 successive-approximation, 475
 trigger, 485
add, 78
add and subtract half-words with exchange, 625
add with carry, 78
ADSR, 511
advanced high-performance bus, 56
Advanced High-performance Bus, 462
advanced peripheral bus, 56
Advanced Peripheral Bus, 462
AHB, 56, 462
AHB/APB bridge, 462
AL, 118
ALIGN, 67, 230
alignment, 229
 ALIGN, 230
 double-word alignment, 229
 half-word alignment, 229
 padding, 229
 padding bytes, 229
 word alignment, 229
alternate function, 686
ALU, 18, 21, 55, 56, 58, 73, 74, 76
AMBA, 462
analog watchdog, 481
APB, 56, 462
application binary interface, 179, 199, 227
application program status register, 74, 117
APSR, 74, 91, 117
AREA, 66
arithmetic
 add, 78
 add with carry, 78
 Boolean operators, 83
 division, 80
 logical shift, 82
 long multiplication, 80
 multiply and subtract, 78

- reverse subtract, 78
- saturation, 81
- subtract, 78
- subtract with carry, 78
- arithmetic logic unit, 55
- ARM32, 52
- ARM64, 53
- Armstrong number, 144
- Armstrong numbers, 159
- Armv8-M, 54
- ASB, 462
- ASCII, 46, 656
- asm, 239
- assembly function in C programs, 239
- assembly instruction, 63
- assembly program, 1
- asynchronous transmission, 521
- AT commands, 537
- atoi, 162
- audio, 582
- automatic stacking, 255
- automatic unstacking, 255
- AVRCP, 536

B

- Barrel shifter, 61, 76, 82
- base, 27, 281
- Base Priority Mask Register, 264
- BASEPRI, 12, 91, 264
- baud rate, 523
- biased exponent, 294
- big endian, 99
- binary coded decimal (BCD), 446
- binary executable, 1
- binary interface, 174
- binary numbers, 27, 29
- binary search, 163
- bipolar stepper motor, 382
- bit, 25
 - bit mask, 84
 - check a bit, 85
 - clear a bit, 86
 - set a bit, 86
 - toggle a bit, 86
- bit field extraction, 92
- bit order, 87
- bit stuffing, 571
- bitwise logic
 - AND, 83
 - bit clear, 83
 - move not, 83
- BL, 121
- Bluetooth, 536
 - address, 536
 - AT commands, 537
 - NULL packet, 536
 - paring, 537
- BLX, 122
- Boolean operators, 83
- boot loader, 17
- booting process, 253
- branch
 - branch if equal, 120, 662
 - branch if negative, 120, 662
 - branch if not equal, 120, 662
 - branch if overflow set, 120, 662
 - branch if positive or zero, 120, 662
 - branch if signed greater or equal, 120, 662
 - branch if signed greater than, 120, 662
 - branch if signed less than, 120, 662
 - branch if signed less than or equal, 120, 662
 - branch if unsigned higher, 120, 662
 - branch if unsigned higher or same, 120, 662
 - branch if unsigned lower, 120, 662
 - branch if unsigned lower or same, 120, 662
 - branch label, 120
 - table branch byte, 132
 - table branch half-word, 132
- branch and exchange, 122, 172
- branch and link, 122, 172
- branch indirect with link, 122
- branch instruction, 119
- break statement, 131
- bridge, 462
- bubble sort, 165
- buffered output, 502
- bulk transfers, 572
- bus, 4, 56
 - AHB, 56, 462
 - AHB/APB bridge, 462
 - AMBA, 462
 - APB, 56, 462
 - ASB, 462
 - bus arbitration, 462, 541
 - bus matrix, 55
- busy-waiting, 250
- BX, 122
- byte addressable, 25
- byte order, 87
- byte selection, 640

C

calendar time, 442
call a C function from assembly, 243
call an assembly subroutine from C, 241
caller, 8, 171, 172
calloc, 7
carry flag, 35, 36, 40, 73
CBNZ, 121
CBZ, 121
CDC, 582
check a bit, 85
circular right rotate, 98
CISC, 51
clear a bit, 86
clock accuracy, 445
clock stretching, 541
clock synchronization, 541
CLZ, 215
CMN, 75, 90
CMP, 75, 90
collector, 359
comment, 2, 19, 61, 62, 63, 659
compare and branch on non-zero, 121
compare and branch on zero, 121
compare negative, 75, 90
compound Boolean expression, 124
compound Boolean expression, 124
concatenate strings, 185
condition flags, 117, 122
conditional branch instruction, 119
conditional execution, 122
context switch, 601, 603, 605, 606, 607
continue statement, 130
control register, 501, 596
control structures, 141
convert string to integer, 162
Cortex-A, 53
Cortex-M, 53
Cortex-M0, 337
Cortex-M4, 337
Cortex-M7, 15
Cortex-R, 53
count digits, 154
count leading zeros, 215
count ones, 150
counter debouncer, 373
counter overflow, 441
counter underflow, 441
CPACR, 311, 312, 313
CPS, 264

CPSID, 264, 597
CPSIE, 264, 597, 599, 607
CRC, 573

D

DA, 105
DAC, 498
 buffered output, 502
 data output register, 501
 glitch, 499
 resolution, 499
 sampling rate, 499
 settling time, 499
 software trigger, 506
 timer trigger, 507
 trigger, 501
Darlington array, 390
data alignment, 229
data comparison, 90
data memory, 7, 21
data minus, 570
data plus, 570
data segment, 3
data size, 26
data symbols, 1
data type, 26
DB, 105
De Morgan's laws, 125
debouncing, 371
decimal, 27, 281
default NaN, 315
deformalized, 297
delay, 271
differential signaling, 525
differential signals, 570
digital quantization, 476
directive, 2, 62, 63, 65, 66, 659
dividing by zero, 276
division (64-bit signed), 221
division (64-bit unsigned), 219
DMA, 493, 533
 ADC, 493
 CCR, 468
 channel, 465
 circular mode, 470
 CMAR, 468
 CNDTR, 468
 CPAR, 468
 data memory, 410
 flow-through, 463

- fly-by, 463
 - hardware priority, 467
 - I²C, 558
 - increment mode, 468
 - interrupt, 471
 - normal mode, 470
 - ping-pong buffering, 495
 - priority, 467
 - software priority, 467
 - software trigger, 466
 - UART, 533
 - DMA and interrupt enable register, 428
 - double buffering, 495
 - double precision, 294
 - double-word, 25
 - do-while loop, 129
 - DSB, 312
 - DSP, 611
 - 16×32 multiply and accumulate, 635
 - 16-bit multiply, 627
 - 32×32 multiply and accumulate, 635
 - add and subtract half-words with exchange, 625
 - byte selection, 640
 - digital filtering, 630
 - dual 16-bit signed multiply with 32-bit accumulate, 633
 - extension and add, 624
 - finite impulse response, 630
 - fixed-point DSP, 611, 612
 - floating-point DSP, 611
 - multiply and accumulate, 635
 - multiply and accumulate, 634
 - multiply and accumulate, 630
 - overflow, 613
 - pack two half-words, 637
 - Q flag, 614
 - Qn format, 612
 - saturation, 613
 - signed extension, 638
 - SIMD, 615, 616
 - sum of absolute difference, 623
 - sum of squares, 631
 - underflow, 613
 - unsigned extension, 638
 - vector absolute value, 642
 - vector dot product, 650
 - vector mean, 647
 - vector min and max, 652
 - vector negate, 641
 - vector offset with saturation, 644
 - vector pairwise multiplication, 648
 - vector shift with saturation, 645
 - wrap-around, 613
 - dual 16-bit signed multiply with 32-bit accumulate, 633
 - duty cycle, 416
- E**
- EABI, 183, 241, 243, 658
 - electromagnetic interference, 362
 - ELF, 2, 3, 657
 - embedded assembly in C programs, 240
 - EMI, 362
 - encoding
 - major opcode, 340
 - minor opcode, 340
 - opcode, 346
 - END, 66
 - end of packet, 573
 - endian, 87, 99, 137, 258
 - ENDP, 66
 - endpoint, 569, 572, 573, 574, 575, 577, 580, 583
 - ENTRY, 66
 - enumeration, 577
 - EOP, 572, 573, 574
 - EPSR, 74, 91
 - EQU, 67, 369
 - equal, 118
 - Euclid's algorithm, 183
 - even parity, 155, 523
 - event generation register, 414
 - EXC_RETURN, 594
 - exception, 250
 - exception handling, 275
 - exception return value, 594
 - executable and linkable format, 2
 - execution program status register, 74
 - execution view, 3
 - export, 69, 182, 241
 - extension and add, 624
 - extern, 69, 242, 244
 - external interrupt, 273
 - external voltage reference, 480
 - EXTI, 272
- F**
- factorial (recursive), 200, 201
 - factorial numbers, 149, 202
 - FAULTMASK, 12, 91
 - FHSS, 536

- find maximum, 152
- finite impulse response, 630
- fixed-point numbers, 282
 - accuracy, 286
 - addition, 288
 - convert from real, 285
 - division, 290
 - multiplication, 289
 - Qm.n format, 284
 - Qn format, 612
 - range, 286
 - resolution, 286
 - rounding, 285
 - subtraction, 288
 - UQm.n format, 283
 - UQn format, 283
- flash memory, 7
- floating-point numbers, 293
 - addition, 304
 - biased exponent, 294
 - double precision, 294
 - fraction field, 294
 - half precision, 294
 - hidden bit, 293
 - IEEE 754 standard, 293
 - multiplication, 308
 - normalized notation, 293
 - overflow, 298
 - range, 299
 - rounding rules, 301
 - rounding to even, 302
 - sign bit, 294
 - single precision, 294
 - special values, 297
 - subnormal numbers, 297
 - underflow, 298
- floating-point register, 311
- floating-point unit, 281
- flowcharts, 144
- flow-through, 463
- fly-by, 463
- for loop, 127
- FPCA, 593
- FPCAR, 311, 315, 317
- FPCCR, 311, 317, 318, 327
- FPSCR, 311, 313, 320, 322
- FPU, 311, 502
 - alternative half-precision, 314, 315
 - APSR_G, 314
 - APSR_NZCV, 314
 - APSR_NZCVQ, 314
 - APSR_NZCVQG, 314
- arithmetic instructions, 321
- comparison, 322
- copy, 320
- CPACR, 311, 312
- default NaN mode, 314, 315
- divide-by-zero exception, 315
- exception handling, 325
- exceptions, 315, 325
- flushing-to-zero, 314
- FPCA, 316
- FPCAR, 311, 315
- FPCCR, 311, 317
- FPSCR, 311, 313
- inexact exception, 315
- input denormal cumulative exception, 315
- invalid operation exception, 315
- lazy stacking, 315, 316, 318
- load, 319
- multiply-accumulate instructions, 322
- N, Z, C, V flags, 314
- overflow exception, 315
- passing arguments, 311
- precision conversion, 323
- registers, 311
- rounding mode, 314
- stack frame, 316
- store, 319
- underflow exception, 315
- VCMP, 322
- VCMPE, 322
- VCVT, 323
- VLDM, 319
- VLDR, 319
- VMOV, 320
- VMRS, 314, 320
- VMSR, 320
- VPOP, 319
- VPUSH, 319
- VSTM, 319
- VSTR, 319
- fraction field, 294
- freeze mode, 486
- frequency hopping, 536
- FT232R, 526
- full descending stack, 108
- full stepping, 384, 385, 386, 388
- full-duplex, 522
- function, 171

G

GAVDP, 536
 GCC, 657
 GCD, 183
 gdb, 657
 GE flags, 639, 640
 general-purpose registers, 12
 get, 69
 global, 241
 global static variable, 233
 goto statement, 141, 143
 GPIO, 355

- data input register, 368
- data output register, 368
- debouncing, 371
- input data register, 355
- keypad scanning, 376
- LED, 366
- output data register, 355
- polling, 374
- pull down, 356
- pull up, 356
- push button, 371
- push pull, 359
- Schmitt trigger, 357
- slew rate, 362
- strong pull down, 356, 376
- strong pull up, 356, 376
- wired-AND, 361
- wired-OR, 361

 greatest common divisor, 183
 gyro, 563
 gyroscope, 563

H

half precision, 294
 half stepping, 386
 half-duplex, 522
 half-word, 25
 Hamming distance, 150
 hard fault handler, 276
 hardware debouncing, 371
 harmonics, 362, 510
 Harvard architecture, 4, 7, 9, 16
 HD44780, 391
 heap, 7, 177
 hexadecimal, 27
 HID, 582
 HID descriptor, 583, 585

high registers, 12

I

I²C, 539

- ACK, 540, 545
- bus arbitration, 541
- clock stretching, 541
- clock synchronization, 541
- data hold time, 548
- data setup time, 547
- DMA, 558
- fall time, 545
- frame, 542
- NACK, 540, 545
- open drain, 539
- polling, 551, 552
- rise time, 545
- SCL, 539
- SDA, 539
- start, 540
- stop, 540
- TC74, 543, 553
- temperature sensor, 543
- timing, 545

 IA, 105
 IB, 105
 ICER, 258
 ICPSC, 428
 if-then statement, 123
 if-then-else statement, 126
 immediate number, 79, 98, 99, 342
 import, 69, 182, 242
 include, 69
 initialized data segment, 7
 injected channel, 485
 inline assembly, 239, 663
 input capture, 425

- prescaler, 428

 insert into sorted array, 187
 instruction memory, 6
 interface class, 575
 intermediate representation, 1
 internal reference voltage, 480
 interrupt, 249

- active bit register, 257
- auto-stacking, 255
- clear pending register, 257
- enable and disable, 258
- external interrupt, 273
- global disable, 264

- global enable, 264
- interrupt handler, 252
- interrupt levels, 261
- interrupt number, 251, 257
- interrupt vector table, 253
- non-maskable interrupts, 264
- pending bit, 258
- peripheral interrupts, 251
- preemption priority, 260
- priority, 255, 260
- set enable register, 257
- set pending register, 257
- software interrupts, 275
- software trigger, 258
- system exceptions, 250
- unstacking, 255
- interrupt clear enable register, 257
- interrupt number, 250
- interrupt priority register, 260
- interrupt program status register, 74
- interrupt service routine, 249
- interrupt stacking, 255
- interrupt transfers, 572
- interrupt unstacking, 255
- interrupt vector table, 666
- intra-procedure-call register, 174, 175
- Inverting Schmitt trigger, 357
- IP, 260
- IPSR, 74, 91
- ISA, 51
- ISB, 312, 594
- ISER, 257, 258
- isochronous transfers, 572, 577, 582
- itoa, 188

J

- J state, 570
- JTAG, 667

K

- keypad reverse scanning, 381
- keypad scanning, 376

L

- L3GD20, 563
- label, 1, 60, 62, 132, 144, 659
- last-in-first-out, 107
- lazy stacking, 315, 316, 318

- LCD, 391
 - 4-bit bus mode, 392
 - 8-bit bus mode, 392
 - commands, 395
 - data bus, 392
 - encoding, 394
 - function set, 395
 - initialization, 396
 - nibble, 393
 - programming fonts, 398
 - register select, 392
 - size, 394
- LDM, 103
 - LDMDA, 105, 110
 - LDMDB, 105, 110
 - LDMIA, 105, 109, 110
 - LDMIB, 105, 110
- LDR, 98
- LDRB, 103, 228, 677, 678
- LDRD, 199
- LDRH, 103
- LDRSB, 103, 228, 677
- LDRSH, 103
- leap second, 442
- LIFO, 107
- linear search, 152
- link register, 12
- linker script, 664
- linking view, 3
- little endian, 99, 258
- live range, 12, 146
- liveness, 146
- load
 - load byte, 103
 - load half-word, 103
 - load multiple words, 103
 - load signed byte, 103
 - load signed half-word, 103
 - load word, 103
- load constant into registers, 97
- load double, 199
- load register with byte, 228
- load register with double-word, 229
- load register with signed byte, 228
- load register with signed half-word, 228
- loading effects, 501
- local static variable, 233, 235
- locality, 11
- logical shift left, 342
- logical shift right, 217
- lookup table, 502

loop
 break, 131
 continue, 130
 do-while loop, 129
 for loop, 127
 while loop, 128

low registers, 12

M

machine program, 1, 2, 4, 16
 main stack, 12, 256, 593, 604
 major opcode, 340
 malloc, 7
 mask, 84
 matrix transpose, 190
 maximum value of an array, 152
 memory
 data memory, 4
 main memory, 4
 memory address modes, 101
 memory addressing modes
 pre-index, 101, 102
 memory map, 9
 memory mapped I/O, 9
 Memory-mapped I/O, 363
 micro-stepping, 388
 minor opcode, 340, 342
 MISO, 560
 MLA, 218
 mnemonic, 2, 60, 61, 75
 modulo, 158
 MOSI, 560
 MOV, 91, 97
 move 16-bit immediate value to bottom half-word, 97
 move from general register to special register, 91
 move from special register to general register, 91
 move not, 91
 move the bitwise inverse of 8-bit immediate value, 97
 MOVW, 97
 MRS, 74, 91
 MSC, 582
 MSR, 74, 91
 multiplication (64 bits), 218
 multiply and accumulate, 635
 multiply and accumulate, 630, 634
 multiply and subtract, 78
 musical
 ADSR, 511
 amplitude, 510
 duration, 511

pitch, 510
 timbre, 510
 tone, 510
 MVN, 91, 97

N

NACK, 540, 545
 NaN, 297
 negative, 118
 negative flag, 73
 nibble, 393
 NMI, 12
 non-maskable interrupt, 261
 non-preemptive, 250
 non-return-to-zero inverted, 570
 non-static variable, 234
 non-system interrupts, 258
 non-volatile, 4, 238
 normalized presentation, 297
 NOT, 91
 not any number, 297
 note equal, 118
 nPRIV, 593
 NRZI, 570
 NULL, 46
 NVIC, 55, 255, 257
 enable interrupt, 274
 Enable IRQ, 605
 set priority, 270
 NVIC_ClearPendingIRQ, 275

O

OCM, 409
 OCREF, 408, 409
 octal, 27
 odd parity, 155, 523
 one's complement, 32
 opcode, 60, 339, 340, 342, 345, 346, 347
 open collector, 539
 open drain, 359, 360, 361, 380, 539
 OpenOCD, 667
 operands, 2, 56
 output compare, 405
 over-capture flag, 428
 overflow, 37, 40
 overflow on subtraction, 38
 overflow clear, 118, 120, 662
 overflow flag, 35, 73
 overflow set, 118

oversampling, 523

P

pack two half-words, 637
 packed, 232
 packed structure, 230
 padding, 68
 palindrome string, 160
 parallel 16-bit add and subtract, 620
 parallel 8-bit add and subtract, 616
 parasitic capacitors, 546
 parity, 155
 even parity, 155
 odd parity, 155
 parity bit, 522
 part per million, 570
 parts per million, 445
 pass by reference, 177, 178, 181
 pass by value, 177, 178, 179, 181
 passing arguments, 176
 PC-relative addressing, 99, 343, 352
 perfect number, 157
 peripheral interrupt, 257, 258, 259, 263
 permutation, 203
 PHDC, 582
 piconet, 536
 ping-pong buffering, 495
 pipeline, 14
 pitch, 563
 PKHBT, 637, 645
 PKHTB, 637
 plus, 118, 120, 662
 polling, 250, 255, 374, 381
 Port-mapped I/O, 363
 positive or zero, 118
 post-index, 101, 104, 185
 pot, 488
 potentiometer, 488
 power dissipation, 475
 PPM, 445, 570
 preempt priority, 261
 preemptive, 250
 pre-index, 101, 104
 pre-index with update, 101, 104
 prescaler, 408
 preserve running environment, 173
 PRIMASK, 12, 91
 Priority Mask Register, 264
 privileged state, 592, 597
 PROC, 66

procedure, 171
 process stack, 12, 256, 593, 604, 608
 processor exception, 257
 program counter, 12, 13
 program status register, 74
 pseudo instruction, 17, 63, 98, 99, 161
 PSR, 74, 91, 255, 602, 604, 607
 pull down, 356
 pull up, 356
 push button, 371
 push pull, 359, 361, 366, 380
 PWM, 416
 alignment, 420
 center-aligned, 420
 control register, 414
 duty cycle, 416, 418
 edge-aligned, 420
 mode, 417
 period, 418
 PWM duty cycle, 418
 PWM period, 418

Q

Q15, 284, 612
 Q31, 612
 Q7, 284, 612
 QADD, 622
 QADD16, 621, 644
 QASX, 626
 QDADD, 622
 Qm.n format, 284
 qNaN, 297
 QSAX, 626
 QSUB, 622
 QSUB16, 621, 642
 QSUB8, 641
 quantization error, 478, 479
 quiet NaN, 297

R

radio frequency interference, 362
 radix, 281
 real number, 25, 281, 286, 295
 real-time clock, 442
 recursive function, 200
 register allocation, 11
 register spilling, 148
 registers, 10
 general purpose registers, 10

- intra-procedure-call register, 175
- scratch registers, 175, 179
- special purpose registers, 10
- virtual registers, 240
- regular channel, 485
- remove duplicate, 194
- reset handler, 252
- Reset_Handler, 666
- resolution, 475
- return address, 172
- reverse bits, 88
- reverse byte order, 88
- reverse subtract, 78
- RFCOMM, 536
- RFI, 362
- RISC, 51
- roll, 563
- ROR, 227
- rotate
 - rotate right, 76
 - rotate right with extend, 77
- Round Robin, 602
- round to closest, 158
- round to even, 302
- round to the nearest, 301
- round toward negative infinity, 301
- round toward zero, 301
- round-robin scheduler, 600, 608
- routine, 171
- RRX, 227
- RS-232, 525
- RS-422, 525
- RTC, 442
 - alarm, 451, 452
 - clock prescaler, 444
 - initialization, 447

S

- S suffix, 75, 87, 345, 347
- SAD, 623
- SADD8, 616, 617
- sample-and-hold amplifier, 476, 477
- sampling rate, 475
- sampling time, 478
- SASX, 626
- saturating add and subtract, 622
- saturation, 81, 613
- saturation flag, 73
- SBC, 214
- SBFX, 92
- scanning algorithm, 377
- SCB, 262
- Schmitt trigger, 357, 358
- scratch register, 175
- scratch registers, 175
- SE0, 571
- SE1, 571
- SEL, 642
- separated operand scanning, 635
- Serial Wire, 667
- servo motor, 382
- set a bit, 86
- shift
 - arithmetic shift right, 76
 - logical shift left, 76
 - logical shift right, 76
- shift and rotate, 76
- shift left (64 bits), 216
- shift right (64 bits), 217
- SHP, 262
- sign and magnitude, 31
- sign extension, 34, 89, 215, 483
 - SXTB
 - extend a byte, 89
 - SXTH
 - extend a half-word, 89
- signaling NaN, 297
- signed bit field extraction, 92
- signed division, 45, 76
- signed greater or equal, 118
- signed greater than, 118
- signed integer, 29
- signed less than, 118
- signed less than or equal, 118
- signed saturate, 78, 81
- SIMD, 615
 - add, 617
 - byte selection, 640
 - extension and add, 624
 - GE flags, 639
 - parallel 16-bit add, 620
 - parallel 16-bit subtract, 620
 - parallel 8-bit add, 616
 - parallel 8-bit subtract, 616
 - saturating add, 619
 - saturating add and subtract, 622
 - saturating subtract, 619
 - signed extension, 638
 - subtract, 616
 - unsigned extension, 638
- sine table, 502

- single precision, 294
- single-ended signal, 571
- single-ended signaling, 525
- single-entry, single-exit, 141
- sinusoidal, 510
- slave select line, 560
- Sleep-on-Exit, 455
- slew rate, 362
- SMLABB, 634
- SMLAD, 648
- SMLALBB, 632
- SMLALD, 630, 651
- SMLAWB, 635
- SMLSLD, 630
- SMMLA, 635
- SMUAD, 628
- SMULBB, 627, 649
- SMULTT, 649
- sNaN, 297
- SOF, 573
- softfp, 658
- software debouncing, 372
- software trigger, 486
- software trigger interrupt register, 257, 258
- spatial locality, 11
- SPI, 560
 - clock configuration, 562
 - clock mode, 563
 - clock phase, 563
 - clock polarity, 563
 - gyro, 563
 - MISO, 560
 - MOSI, 560
 - SCLK, 560
- spilling, 148
- SPSEL, 593, 596
- SSAT, 73, 78, 81
- SSAT16, 614
- SSAX, 626
- SSUB16, 643
- SSUB8, 642
- stack, 8, 107
 - ascending stack, 107
 - definition, 107
 - descending stack, 107
 - empty stack, 108
 - full stack, 107
 - function call, 174
 - interrupt stacking, 255
 - interrupt unstacking, 255
 - main stack, 109, 593
 - MSP or PSP, 593
 - pass arguments via stack, 198
 - preserve LR, 179
 - process stack, 593
 - recursive function, 202
 - stack frame, 227
 - stack pointer, 12
- stack frame pointer, 604
- start-of-frame, 573
- static variable, 233
- statically-allocated, 3
- stepper motor, 382
 - full stepping, 383, 385
 - half stepping, 386
 - micro-stepping, 388
 - step angle, 383
 - wave stepping, 385
- stepwise refinement, 144
- sticky, 75
- STIR, 257, 258
- STM, 103
 - STMDA, 105, 110
 - STMDB, 105, 109, 110, 606, 607
 - STMIA, 105, 110
 - STMIB, 105, 110
- store
 - store lower byte, 103
 - store lower half-word, 103
 - store multiple words, 103
 - store register byte, 228
 - store register half-word, 228
 - store word, 103
- STR, 103
- STRB, 103
- strcat, 185, 204
- strcmp, 186
- STRH, 103
- string, 46
 - comparison, 47, 186
 - concatenate, 185, 204
 - convert string to integer, 162
 - isDigit, 47
 - isLower, 47
 - isUpper, 47
 - isWhitespace, 47
 - itoa, 188
 - permutation, 203
 - remove a character, 192
 - strlen, 48, 241, 243
 - toLowerCase, 48
 - toUpperCase, 48

strlen, 241, 243
 strong pull down, 356, 376
 strong pull up, 356, 376
 structured programming, 141
 st-util, 667
 subroutine, 171, 172

- pass by reference, 177
- pass by value, 177
- passing arguments, 176
- preserve running environment, 173

 subtract, 78
 subtract with carry, 78
 successive-approximation, 475
 suffix S, 122
 sum of absolute difference, 623
 supervisor call, 276
 SVC, 597
 swap, 181, 194
 SWI, 597
 switch statement, 132
 SXTAB, 624
 SXTAB16, 625
 SXTAH, 624
 SXTB, 624
 SXTH, 624
 synchronous protocol, 560
 system control block, 262
 system exception, 257
 system handler priority, 262
 system interrupt, 257
 system tick timer, 265
 SysTick, 237, 265

- calibration register, 267
- control and status register, 266
- current value register, 267
- initialization, 270
- interrupt handler, 272
- reload value register, 267

T

table branch half-word, 132
 tail recursive, 205
 TBB, 132
 TBH, 132
 TC74, 543, 553
 temporal locality, 11
 TEQ, 75, 90
 test, 90
 test equivalence, 90
 text segment, 3

the Fault Mask Register, 264
 Thumb, 52, 337

- bit stream, 338

 Thumb-2, 52, 54, 337

- 16-bit encoding, 339
- 32-bit encoding, 340
- bit stream, 338
- decode, 344

 timer, 405

- center-aligned counting, 406
- compare output, 408
- complementary output, 413
- complementary output, 409
- digital input filter, 427
- DMA, 430
- down-counting, 406
- input capture, 425, 434
- main output, 409
- mode, 409
- noise filtering, 428
- OCM, 409
- OCREF, 408
- output compare, 405
- over-capture flag, 428
- overflow, 407
- prescaler, 408, 430
- PWM, 416
- UEV, 414
- underflow, 407
- up-counting, 406
- update event, 414

 toggle a bit, 86
 token packet, 573
 transmission bus, 4
 trap, 276

- hard fault, 276

 trap handler, 325
 truncation towards zero, 154
 TrustZone, 54
 TST, 75, 90
 two's complement, 33

U

UAL, 660
 UART, 521

- asynchronous transmission, 521
- baud rate, 523
- Baud rate register, 524
- DMA, 533
- frame, 522

- full-duplex, 522
- half-duplex, 522
- interrupt, 530
- parity bit, 522
- polling, 526
- stop bit, 523
- UASX, 626
- UBFX, 92
- ULN2803, 390
- ultrasonic distance sensor, 436
- ultrasonic waves, 436
- UMAAL, 636
- UMLAL, 81
- UMULL, 81
- unaligned memory accesses, 232
- unaligned memory layout, 232
- unconditional branch instruction, 119
- Unified Assembly Language, 660
- uninitialized data segment, 7
- uninitialized variables, 3
- unipolar stepper motor, 382
- unique numbers, 194
- Unix Epoch, 460
- unprivileged state, 592, 597
- unsigned decimal, 29
- unsigned division, 45, 76
- unsigned field extraction, 92
- unsigned higher, 118
- unsigned higher or same, 118
- unsigned lower, 118
- unsigned lower or same, 118
- unsigned numbers, 29
- unsigned saturate, 78, 81
- update event, 441
- update interrupt flag bit, 414
- UQADD16, 621
- UQASX, 626
- UQm.n format, 283
- UQn format, 283
- UQSAX, 626
- USAD8, 623
- USADA8, 623
- USAT, 73, 78, 81
- USAT16, 614
- USAX, 626
- USB, 569
 - address field, 573
 - bulk transfers, 572
 - bus layer, 570
 - class layer, 582
 - CRC, 573

- data field, 573
- descriptors, 574
- device layer, 572
- differential signals, 570
- endpoint, 572, 577
- enumeration, 577
- functions layer, 574
- GET_DESCRIPTOR requests, 580
- HID, 582
- interrupt transfers, 572
- isochronous transfers, 572
- J state, 570
- NRZI, 570
- packet identification field, 573
- power supply, 575
- product ID, 575
- SET_ADDRESS request, 580
- speed, 570
- start-of-frame, 573
- SYNC, 573
- transfer type, 572
- vendor ID, 575
- USB OTG, 569
- UTC, 442, 443
- UXTAB, 624
- UXTAB16, 625
- UXTAH, 624
- UXTB, 624
- UXTH, 624

V

- variable live range, 12
- vector absolute value, 642
- vector dot product, 650
- vector mean, 647
- vector min and max, 652
- vector negate, 641
- vector offset with saturation, 644
- vector pairwise multiplication, 648
- vector shift with saturation, 645
- video, 582
- virtual registers, 240
- VMRS, 314
- volatile, 4, 5, 233, 237, 238, 364, 415
- von Neumann, 4

W

- wait for event, 240, 455
- wait for interrupt, 240, 455

watchdog, 481
wave stepping, 385
weak, 242, 243, 244
WFE, 455
WFI, 455
while loop, 128
wired-AND, 361
wired-OR, 361
word, 25

X

xPSR, 12

Y

yaw, 563
year 2038 problem, 442

Z

zero extension, 89
 UXTB
 extend a byte, 89
 UXTH
 extend a half-word, 89
zero flag, 73
zero-initialized data section, 7
zero-initialized data segment, 3