

ECE 471 – Embedded Systems

Lecture 13

Vince Weaver

`https://web.eece.maine.edu/~vweaver`

`vincent.weaver@maine.edu`

27 September 2023

Announcements

- Don't forget homework #4



Homework #3 Review – Exit in Assembly

- Exit – value is an integer which goes into r0
- Note it is an integer, not ASCII
- Be sure to comment your code and fix any wrong comments
- Note: ABI says value going into r0 is first argument, not the return value



Homework 3 – ARM32 vs THUMB2

- be sure to specify base!
- ARM32 – $0x1048C - 0x1041c = 0x70 = 112$ bytes
- Thumb2 – $0x1046C - 0x10414 = 0x58 = 88$ bytes
Note on new compiler programs might be loaded at 0x500 instead
- Note it's bytes not bits. Also no need to divide by 4.
Also each hex digit is a nibble
- Differences?
 - Thumb2 some instructions are 16-bit rather than 32-



bit

- Thumb2 different instructions (like movt/movw)



Homework 3 – Code Density

- You need to run `strip` on this to see it. Why?
Debug info, including extra thumb debug as well as the longer filename.
- You can use `readelf -a` and `readelf -s` to see the space the various segments take up.
Look at executables, **not** the C source code.



Homework 3 – Code Sizes

arch	unstripped	stripped
C arm32	10,336	5560
C thumb2	10,340	5560
asm arm32	1,308	536
C static	519,372	493,820
C ARM64	70,480	67,600

- You would think THUMB2 would be much smaller, but the assembler makes some poor decisions about wide/narrow instructions.



- Reference my LL work
- C code is larger, but also remember to include the C library:

```
ls -lart /lib/arm-linux-gnueabi/libc-2.31.so  
-rwxr-xr-x 1 root root 1321488 Sep  8 09:17 /lib/arm-linux-gnueabi/libc-2.31.so
```

- There are embedded C libraries, musl, newlib, uclibc, which are much smaller and often used in embedded systems.
- Smallest possible executable? I have written 128 Byte ones for competitions but you have to do sketchy things to the ELF file to be that small



Homework 3 – gdb

- crashes!
- have to use awful gdb interface
- line 9 is the crash
- the assembly is

```
ldr r3, [r3]
```

load byte from the 32-bit address pointed to by r3, store the resulting zero-extended byte into r3 (replacing the old value)

- if you look at src code or info assem you can see it's



dereferencing (following) a NULL (uninitialized) pointer, which is always a segfault on Linux

- Note in this particular case it's not an "off the end of the array" issue, but rather the array doesn't exist at all problem
- Don't confuse NUL terminated strings with invalid NULL pointers



Homework 3 – Something Cool

- How would you convert `print_number` to hexadecimal?
- Is it easier to divide by 16 than 10? Especially w/o a divide instruction?
- Yes, shift and masks. Trick part is to special case 10 to 15 to be A to F
- If read with `scanf()`, do you handle negative numbers?
Do you handle floating point numbers?
Characters? Hex numbers?



Homework 3 – Linux Tools – cal 9 1752

- Debian Linux dropped “cal” from the default install, it’s now in the “ncal” package
- cal missing days
- Julian to Gregorian calendar.
- People sad who paid weekly but paid rent monthly.
- George Washington’s birthday
- Hunt for Red October
- Beware believing any page you google. Some urban legends / joke sites about this. If it were some sort of



programmer bug it would have been fixed years ago.



Briefly reviewed Virtual Memory from Last Time



Coding Directly for the Hardware

One way of developing embedded systems is coding to the raw hardware, as you did with the STM Discovery Boards in ECE271.

- Compile code
- Prepare for upload (hexbin?)
- Upload into FLASH
- Boots to offset



- Setup, flat memory (usually), stack at top, code near bottom, IRQ vectors
- Handle Interrupts
- Must do I/O directly (no drivers)
Although if lucky, can find existing code.
- **Code is specific to the hardware you are on**



Instead, one can use an Operating System



Why Use an Operating System?

- Provides Layers of Abstraction
 - Abstract hardware: hide hardware differences. same hardware interface for classes of hardware (things like video cameras, disks, keyboards, etc) despite differing implementation details
 - Abstract software: with VM get linear address space, same system calls on all systems
- Other benefits:
 - Multi-tasking / Multi-user



- Security, permissions (Linus dial out onto /dev/hda)
- Common code in kernel and libraries, no need to re-invent
- Handle complex low-level tasks (interrupts, DMA, task-switching)



Downsides of Operating System?

- Overhead / Abstraction has a cost
 - Higher overhead (speed)
 - Higher overhead (memory)
 - Unknown timing (Real Time)
- Security
 - Larger code base can provide larger attack surface



Other Aspects of Operating Systems

- What about other things?
 - Easy to code for? Provide examples
 - Nice GUI interface? Sometimes



What's included with an OS

- kernel / drivers (syscall barrier) – Linux definition
- also system libraries – Solaris definition
- low-level utils / software / GUI – Windows definition
Web Browser included?
- Linux usually makes distinction between the OS Kernel and distribution. OSX/Windows usually doesn't.



Bypassing Linux to hit hardware directly

- Linux does not support things like pullups, but people have written code that will poke the relevant bits directly.



Bypassing Linux for speed

<http://codeandlife.com/2012/07/03/benchmarking-raspberry-pi-gpio-speed/>

Trying to generate fastest GPIO square wave.

shell	gpio util	40Hz
shell	sysfs	2.8kHz
Python	WiringPi	28kHz
Python	RPi.GPIO	70kHz
C	sysfs (vmw)	400kHz
C	WiringPi	4.6MHz
C	libbcm2835	5.4MHz
C	Rpi Foundation "Native"	22MHz



Operating Systems Types

- Monolithic kernel – everything in one big address space. Something goes wrong, lose it all. Faster
- Microkernel – separate parts that communicate by message passing. can restart independently. Slower.
- Microkernels were supposed to take over the world. Didn't happen. (GNU Hurd?)
- Famous Torvalds (Linux) vs Tannenbaum (Minix) flamewar



Common Desktop/Server Operating Systems

- Windows
- OSX
- Linux
- FreeBSD / NetBSD / OpenBSD
- UNIX (Irix/Solaris/AIX/etc.)
- BeOS/Haiku



Embedded Operating Systems

- Microsoft WinCE, Windows Mobile
- Linux / Android
- VXworks – realtime OS, used on many space probes
- Apple iOS
- QNX – realtime microkernel UNIX-like OS, owned by Blackberry now
- Cisco iOS
- ThreadX – found in Pi GPU



Embedded Linux Distributions

- linaro – consortium that work on ARM software
- openwrt – initially designed for wireless routers
- yocto – Linux Foundation sponsored embedded distro
- maemo – embedded distro originally by Nokia (obsolete)
- MeeGo – continuation of maemo, also obsolete
- Tizen – Follow up on MeeGo, by Samsung and Intel
- Ångstrom – Merger of various projects
- And many others. It's very easy to put together a Linux distribution

