

# ECE 574 – Cluster Computing

## Lecture 1

Vince Weaver

`http://web.eece.maine.edu/~vweaver`

`vincent.weaver@maine.edu`

17 January 2017

# ECE574

- Distribute and go over syllabus

[http://web.eece.maine.edu/~vweaver/classes/ece574\\_2017s/ece574\\_2017s.pdf](http://web.eece.maine.edu/~vweaver/classes/ece574_2017s/ece574_2017s.pdf)

- Grading

- Homeworks, 50% – 11, lowest dropped.

Generally will be due on Thursday by beginning of class. Will usually have at least a week to do them.

Submission by e-mail, grades sent in response to that e-mail, if you don't like that let me know.

Will send out e-mail when assignment posted on



website.

- Midterm, 10%, around spring break?
- Final, 15 (maybe last week of classes?)%
- Class participation: 5%
- Project, 20%. More details as we get closer.
- Late work penalty
- Class notes will be posted on the website.
- Will be handing out computer accounts, please use them



responsibly.

- Will involve C coding.



# Cluster Computing

What is cluster computing?

Basically it's just a large number of computers working together.

So why is that interesting?



# Supercomputers/HPC

InsideHPC defines HPC: “High Performance Computing most generally refers to the practice of aggregating computing power in a way that delivers much higher performance than one could get out of a typical desktop computer or workstation in order to solve large problems in science, engineering, or business.”

And a supercomputer is similarly vague, just a larger computer than the kind you’d normally use.



# Related terms

- Supercomputer – a large computer. No real definition, “I know one if I see one” .
- High Performance Computing – a large computer
- Cluster – one way to make a large computer out of many small computers
- Grid computing – idea to make computing like the power grid, a utility you access to run your jobs. A large loosely coupled cluster.



- Cloud computing – more or less a newer and more buzzword-friendly term for grid computing. Often uses virtualization, not often used for high performance mostly because usually the network is not optimized in a cluster fashion.
- Datacenter – a large building with lots of network connected computers. Not a cluster unless they are working together. This gets complicated when things like google are involved.
- Mainframe – a type of large computer. Usually





differentiated from a supercomputer because a mainframe concentrates on reliability and I/O performance rather than CPU performance.

- Distributed systems – a system that is made out of many subnodes that communicate by passing messages to work on large problems. Sort of the old CS term for cluster computing.
- Parallel computing



# Cluster Definitions?

- Bunch of computers hooked together.
- Commodity Cluster – a large number of off-the-shelf machines hooked up via cheap off-the-shelf network (usually Ethernet)
- as opposed to a custom cluster that will be custom hardware and custom fast network.



# HPC Workloads

- Linear Algebra
- Modeling (weather, chemistry, biology, nuclear, aerospace)
- Business (high-speed trading)
- Simulation
- 3d rendering (movie studios, games)
- Data crunching (geology exploring)



# A little history

- 1960s Seymour Cray (interesting guy) CDC6600 (parallel) and 7600 (pipelined) and Cray 1 (vector) 1976.
- 1970s-1980s – clustered minicomputers, DEC, IBM, Tandem
- 1990s SGI = NUMA
- 1994 Beowulf clusters  
Beowulf was a 1994 NASA project to build a gigaflop



for less than \$50k. Managed a 16-node 486 cluster for \$40k. (comparison – raspberry pi 2 gives you a gigaflop for \$35).

D.J. Becker and T. Sterling and D Savarese and J.E. Dorband and U.A. Ranawak and C.V. Packer  
“BEOWULF: A parallel workstation for scientific computation”

Usually cheap headless off-the-shelf computers connected by Ethernet. Commodity cluster.




# Are all supercomputers clusters?

Not necessarily, though trends have been taking things that way. *High Performance Computing: Crays, Clusters, and Centers. What Next?* by Bell and Gray, 2001. They propose that everything was converging to all clusters, all the time for all supercomputer needs.

In a fairly strongly worded rebuttal, Dongarra, Sterling, Simon and Strohmaier ( *High performance computing: Clusters, constellations, MPPs, and future directions* (2003)) said that no, the world is more complex than



that and commodity clusters are not the end word.



# Supercomputer Features?

- From Dongarra et al.
- Is it clustered? meaning identical grouped together  
c for commodity, m monolithic
- How is the namespace organized?  
distributed means local variables on one node not visible  
on other  
d distributed, s shared, c cache coherent





- How is the parallelism?

t for multithreading, v for vector, c communicating sequential

s systolic, w for VLIW, h for producer/consumer, p parallel process

- How does it handle latency/locality?

c caches, v vectors, t multithreaded, m for processor in memory.

f for prefetching, etc



# Top500 List



# Top500 History

- In 1994, 20% single-cpu, 50% SMP, 24% MPP, 7% SIMD
- In 1997, 0% single-cpu, 43% SMP, 0.5% cluster, 54% MPP, 0.5% SIMD
- in 2002, 40% Constellations, 18% cluster, 40% MPP
- in 2015, 90% cluster, 12% MPP

Definitions from Dongarra et al.



Cluster – system where inter-node communication is 10-1000 times slower than local memory access. (bell and gray)

- single-cpu = just one serial CPU
- simd = single instruction multiple data
- SMP = symmetric multiprocessing, more than one processor
- MPP = massive parallel programming, one machine with lots and lots of processors (see SGI)



- cluster = number of nodes outnumbers number of CPUs per node (dominant programming style distributed, MPI)
- constellation = each node has more CPUs than total nodes (dominant programming style would be multithread, OpenMP)



# Software Concerns

- One OS image or multiple?
- single/smp/mpp = one image
- cluster = each node has own copy of operating system
- Shared memory (just write to memory and all cores can see it, hard work in hardware) vs Message Passing (have to explicitly send data before others see it, hard work in software)



# Heterogeneous Computing

- Unequal nodes
- ARM big/little
- clusters with GPUs
- xeon-phi (almost like a cluster on a PCIe card)



# Example Top500 Listing

- From the November 2002 list, entry #332
- Location: Orono, ME
- Proc Arch: x86
- Proc Type: Pentium III, 1GHz
- Total cores: 416
- RMax/RPeak: 225/416 GFLOPS
- Power: ???
- Accelerators: None

